





# Accessories

PROTRXion™ Series | Technical Data Sheet

	Universal PROTRXion™ Mounting Bracket	M10 to M8 Terminal Adapter	M8 Terminal Blocks and Mounting Screws	M12 to NMEA 2000 Adapter
<b>Picture (not to scale)</b>				
<b>Part Number</b>	03-59293-001	03-59307-001	91006-902 & 91006-901	903-09518-001
<b>Compatible Battery Models</b>	S/M-24V80-TRX S/M-24V90-TRX S/M-36V80-TRX S/M-48V60-TRX S/M-48V60-TRX-HD	S/M-24V80-TRX S/M-24V90-TRX S/M-36V80-TRX S/M-48V60-TRX	S-12V100-TRX-HD S/M-24V60-TRX S/M-24V80-TRX* S/M-24V90-TRX* S/M-36V80-TRX* S/M-48V60-TRX* S/M-48V60-TRX-HD	S-12V100-TRX-HD S-36V80-TRX
<b>Dimensions (nominal)</b>	224-399mm (adjustable) x 36mm x 30mm	Aluminum Plate: 65mm x 20mm x 4mm Machine Screw: M8x1.25x30mm	2X Terminal Block: 46mm x 47.5mm x 43mm	Cable Length: 152mm
<b>Recommended Torque</b>	8.5±0.5 Nm	17.0±1.0 Nm	17.0±1.0 Nm	0.6 Nm max
<b>Continuous Current (max)</b>	N/A	240A	150A	Communication Only

\*Compatible when used with M10 to M8 Terminal Bolt Adapter

	M12 90° Twisted & Shielded Battery to Battery Communication Cable	2m Battery to Battery Communication Extension Cable
<b>Picture (not to scale)</b>		
<b>Part Number</b>	903-09458-001	03-59225-001
<b>Compatible Battery Models</b>	S/M-24V60-TRX S/M-24V80-TRX S/M-24V90-TRX S/M-36V80-TRX S/M-48V60-TRX†	S/M-48V60-TRX-HD
<b>Cable Length</b>	0.6 meters	2.0 meters
<b>IP Rating (mated)</b>	IP67	IP67
<b>Max Continuous Current (per pin)</b>	2A	5A
<b>Connector</b>	TE T4113002081-000	Deutsch DTM06-08SA Deutsch DTM04-08PA
<b>Mating Connector</b>	TE T4131012081-000	Deutsch DTM06-08SA Deutsch DTM04-08PA



Request more Information

inventuspower.com | info@inventuspower.com | +1 877.423.4242

	M12 CAN Terminator	Deutsch CAN Terminator	12V Aux DC Cable Harness with CAN Terminator
<b>Picture (not to scale)</b>			
<b>System &amp; Battery CAN Termination Part Number</b>	03-59024-001	903-09322-002	903-09526-001
<b>System and Battery CAN Termination Pins</b>	<p>120 Ω Pin 1 —  — Pin 2</p> <p>120 Ω Pin 6 —  — Pin 7</p>	<p>120 Ω Pin 1 —  — Pin 2</p> <p>120 Ω Pin 6 —  — Pin 7</p>	<p>120 Ω Pin 1 —  — Pin 2</p> <p>120 Ω Pin 6 —  — Pin 7</p>
<b>Battery CAN Termination Part Number</b>	903-09024-002	03-59322-001	N/A
<b>Battery CAN Termination Pins</b>	<p>120 Ω Pin 6 —  — Pin 7</p>	<p>120 Ω Pin 6 —  — Pin 7</p>	N/A
<b>Compatible Battery Models</b>	S-12V100-TRX-HD S/M-24V80-TRX S/M-24V90-TRX S/M-36V80-TRX S/M-48V60-TRX <sup>†</sup>	S/M-48V60-TRX-HD	S/M-48V60-TRX-HD
<b>Dimensions (max)</b>	43mm x 40mm x 20.2mm	52mm x 32.1mm x 20.7mm	52mm x 32.1mm x 20.7mm 12VDC: 16 AWG x 120mm
<b>IP Rating (mated)</b>	IP67	IP67	IP66
<b>Resistance</b>	120 Ω	120 Ω	120 Ω
<b>Connector</b>	TE T4113002081-000	Deutsch DTM04-08PA	Deutsch DTM04-08PA
<b>Mating Connector</b>	TE T4131012081-000	Deutsch DTM06-08SA	Deutsch DTM06-08SA

<sup>†</sup>Compatible with newer models of S/M-48V60-TRX (MFG Date after March 1, 2023) where pin 8 is auxiliary power

Inventus Power reserves the right to make adjustments to this document at any time, without notice or obligation. All data in this publication is for reference use only. Models may vary from shown.



**Request  
more Information**

**inventuspower.com | info@inventuspower.com | +1 877.423.4242**